

DHI-VTO2201F-P

IP Villa Door Station



- · Anodized alumimum front panel
- CMOS low illumination 2MP HD colorful 140° camera
- Video intercom function
- Access control function that supports two locks
- Mobile phone app, talk to the visitor or unlock the door remotely on your phone
- IK07& IP65
- Support H.265

Audio Compression

- Support surface and flush mount
- PoE



G.711a; G.711u; PCM

Main Processor Embedded processor Operating System Embedded Linux Operation System Button Type Mechanical Interoperability ONVIF; CGI Network Protocol SIP; P2P; IPv4; UPnP; SNMP; DNS; DDNS; RTSP; RTP; TCP; UDP Basic Camera 1/2.9" 2MP CMOS Low Illumination HD Colorful Camera Field of View Horizontal: 138.6"; vertical: 79.6; diagonal:159" Focal Length 2.0 mm WDR 120 dB Noise Reduction 3D NR Video Compression H.265 Video Resolution 50Hz: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR Day/Night Auto (ICR)	Technical Specification	Technical Specification		
Operating SystemEmbedded Linux Operation SystemButton TypeMechanicalInteroperabilityONVIF; CGINetwork ProtocolSIP; P2P; IPv4; UPnP; SNMP; DNS; DDNS; RTSP; RTP; TCP; UDPBasicT/2.9" 2MP CMOS Low Illumination HD Colorful CameraField of ViewHorizontal: 138.6"; vertical: 79.6; diagonal:159"Focal Length2.0 mmWDR120 dBNoise Reduction3D NRVideo CompressionH.265Video Resolution50Hz: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps)Video Frame Rate25 fpsVideo Bit Rate256 Kbps to 8 MbpsLight CompensationAuto IR	System			
Button Type Mechanical Interoperability ONVIF; CGI Network Protocol SIP; P2P; IPv4; UPnP; SNMP; DNS; DDNS; RTSP; RTP; TCP; UDP Basic Camera 1/2.9" 2MP CMOS Low Illumination HD Colorful Camera Field of View Horizontal: 138.6°; vertical: 79.6; diagonal:159° Focal Length 2.0 mm WDR 120 dB Noise Reduction 3D NR Video Compression H.265 Video Resolution SOH2: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60H2: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	Main Processor	Embedded processor		
Interoperability Network Protocol SIP; P2P; IPv4; UPnP; SNMP; DNS; DDNS; RTSP; RTP; TCP; UDP Basic Camera 1/2.9" 2MP CMOS Low Illumination HD Colorful Camera Field of View Horizontal: 138.6°; vertical: 79.6; diagonal:159° Focal Length 2.0 mm WDR 120 dB Noise Reduction 3D NR Video Compression H.265 Video Resolution Video Resolution SOH2: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60H2: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	Operating System	Embedded Linux Operation System		
Network Protocol SIP; P2P; IPv4; UPnP; SNMP; DNS; DDNS; RTSP; RTP; TCP; UDP Basic Camera 1/2.9" 2MP CMOS Low Illumination HD Colorful Camera Field of View Horizontal: 138.6°; vertical: 79.6; diagonal:159° Focal Length 2.0 mm WDR 120 dB Noise Reduction 3D NR Video Compression H.265 Video Resolution 50Hz: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	Button Type	Mechanical		
Basic Camera 1/2.9" 2MP CMOS Low Illumination HD Colorful Camera Field of View Horizontal: 138.6°; vertical: 79.6; diagonal:159° Focal Length 2.0 mm WDR 120 dB Noise Reduction 3D NR Video Compression H.265 Video Resolution 50Hz: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	Interoperability	ONVIF; CGI		
Camera 1/2.9" 2MP CMOS Low Illumination HD Colorful Camera Field of View Horizontal: 138.6°; vertical: 79.6; diagonal:159° Focal Length 2.0 mm WDR 120 dB Noise Reduction 3D NR Video Compression H.265 Video Resolution 50Hz: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	Network Protocol			
Field of View Horizontal: 138.6°; vertical: 79.6; diagonal:159° Focal Length 2.0 mm WDR 120 dB Noise Reduction 3D NR Video Compression H.265 Video Resolution 50Hz: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	Basic			
Focal Length 2.0 mm WDR 120 dB Noise Reduction 3D NR Video Compression H.265 Video Resolution 50Hz: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	Camera	1/2.9" 2MP CMOS Low Illumination HD Colorful Camera		
WDR 120 dB Noise Reduction 3D NR Video Compression H.265 Video Resolution 50Hz: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	Field of View	Horizontal: 138.6°; vertical: 79.6; diagonal:159°		
Noise Reduction 3D NR Video Compression H.265 50Hz: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	Focal Length	2.0 mm		
Video Compression H.265 50Hz: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	WDR	120 dB		
Video Resolution 50Hz: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	Noise Reduction	3D NR		
Video Resolution Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps) Video Frame Rate 25 fps Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	Video Compression	H.265		
Video Bit Rate 256 Kbps to 8 Mbps Light Compensation Auto IR	Video Resolution	Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz:		
Light Compensation Auto IR	Video Frame Rate	25 fps		
	Video Bit Rate	256 Kbps to 8 Mbps		
Day/Night Auto (ICR)	Light Compensation	Auto IR		
	Day/Night	Auto (ICR)		

Audio Input	1 channel
Audio Output	Built-in speaker
Audio Mode	2-way voice communication
Audio Enhancement	Echo suppression/digital noise reduction
Audio Bit Rate	16 KHz, 16 Bit
Status Indicator Light	3
Port	
RS-485 Port	1
Alarm Output	1
Power Output	1-ch 12 VDC 100mA
Exit Button	1
Door Status Detection	1
Lock Control	1
Network Port	One RJ45 10M/100M network port
General	
Appearance color	Silver
Power Supply	DC 12V-24V 1A; Standard PoE
Power Adapter	Optional
Installation	Flush/surface mount
Certifications	CE; FCC; UL

VTO2 Series | DHI-VTO2201F-P

Accessory	Flush/surface mount	
Product Dimensions	130 mm × 96 mm × 28.5 mm (5.12" × 3.78" × 1.12")	
Protection	IK07; IP65	
Operating Temperature	-30°C to +60°C (-22°F to 140°F)	
Operating Humidity	10%–90% (RH, non-condensing)	
Operating Altitude	0 m-3000 m	
Power Consumption	≤ 6W	
Net Weight	0.35 kg (0.77 lb)	
Gross Weight	0.4 kg (0.88 lb)	

Ordering Information				
Туре	Model	Description		
IP Villa Door Station	DHI-VTO2201F-P	2Mp Non Issue card IP Villa Door Station		
Accessories	VTM114	Flush Mounted Box		
	VTM115	Surface Mounted Box		
	VTM05R	Surface-mounted rain cover for VTO2202F		

Dimensions (mm[inch])











